





CITEL



Type 2 AC surge protector - 3-phase

DS43S-400

- Discover our latest innovation : the [DAC50S-30-440](#)
- Type 2 AC Multipolar surge protector
- In: 20 kA
- I_{max} total: 120 kA
- Pluggable module for each phase
- Remote signaling
- EN 61643-11, IEC 61643-11, UL1449 ed.5



Electrical Characteristics		
Network		230/400V
AC system		IT
Nominal line voltage	Un	400 Vac
Max. AC operating voltage	Uc	440 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	580 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	770 Vac disconnection
Residual Current <i>Leakage current to Ground</i>	I _{pe}	< 1.5 mA
Follow current	I _f	None
Nominal discharge current <i>15 x 8/20 µs impulses</i>	I _n	20 kA
Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	I _{max}	40 kA
Connection mode(s)		L/PE
Protection mode(s)		Common mode
Residual voltage at 5 kA <i>@ 5 kA (8/20µs)</i>	Up-5kA	1.3 kV
Protection level L/PE <i>@ I_n (8/20µs)</i>	Up L/PE	1.8 kV
Admissible short-circuit current	I _{sc}	25 000 A
Mechanical Characteristics		
SPD configuration		3-phase
Connection to Network		By screw terminals: 2.5-25mm ² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole
Spare module(s)		DSM40-400
Remote signaling of disconnection		Output on changeover contact
Weight		0.286 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses type gG - 50 A
Standards		
Certification		UL / TUV
Environmental standards		EU RoHS
Part number		
461423		

