





CITEL

Type 2 AC surge protector - 3-phase+N

DS44S-230



- Discover our latest innovation : the [DAC50S-40-275](#)
- Type 2 AC Multipolar surge protector
- In : 20 kA
- I_{max} total : 160 kA
- Pluggable module for each phase
- Remote signaling
- EN 61643-11, IEC 61643-11 compliance
- UL1449 ed.5



Electrical Characteristics		
SPD type	IEC	2
Network		230/400V
AC system		TNS
Nominal line voltage	Un	230 Vac
Max. AC operating voltage	Uc	250 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection
Residual Current	I _{pe}	< 2 mA
Leakage current to Ground		
Follow current	I _f	None
Nominal discharge current 15 x 8/20 µs impulses	I _n	20 kA
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	40 kA
Total Maximum discharge current max. total withstand @ 8/20 µs	I _{max} Total	160 kA
Connection mode(s)		L/PE and N/PE
Protection mode(s)		Common mode
Residual voltage at 5 kA @ 5 kA (8/20µs)	Up-5kA	0.9 kV
Protection level N/PE @ I _n (8/20µs)	Up N/PE	1.25 kV
Protection level L/PE @ I _n (8/20µs)	Up L/PE	1.25 kV
Admissible short-circuit current	I _{sc}	25 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		3-phase+Neutral
Connection to Network		By screw terminals: 2.5-25mm ² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole
Spare module(s)		DSM40-230
Remote signaling of disconnection		Output on changeover contact
Dimensions		See diagram
Weight		0.343 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses type gG - 50 A
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		cRUus
Environmental standards		EU RoHS
Part number		
461522		

