






- ✦ Type 2 surge protector for PV
- ✦ In: 15kA / Imax: 40kA
- ✦ Pluggable
- ✦ Remote signaling
- ✦ IEC 61643-31, EN 61643-31, EN 50539-11 and UL1449 ed.5 certified



V: High-energy varistor
Ft: Thermal fuse
t*: Thermal disconnection system
MI: Disconnection indicator C: Remote signal contact

Electrical Characteristics

SPD type	IEC	2
Network		PV 1250 Vdc
Nominal PV voltage	Uocstc	1250 Vdc
Max. PV operating voltage	Ucpv	1500 Vdc
Residual Current Leakage current to Ground	Ipe	< 0.2 mA
PV Permanent Operating current Current consumption at Ucpv	Icpv	< 0.1 mA
Follow current	If	None
Nominal discharge current 15 x 8/20 µs impulses	In	15 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	40 kA
Current withstand short circuit PV	Iscpv	15 000 A
Connection mode(s)		+/-/PE
Protection mode(s)		Common/Differential mode
Protection level +/- @ In (8/20µs)	Up	5.3 kV

Mechanical Characteristics

Technology		MOV
Connection to Network		By screw terminals: 2.5-25mm ² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection SPD of the PV line
Disconnection indicator		3 mechanical indicators
Spare module(s)		DSM50PV-1500/51
Remote signaling of disconnection		Output on changeover contact
Dimensions		See diagram
Weight		0.334 kg

Disconnectors

Thermal disconnector		Internal
Back-up protection device		Without

Standards

Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5
Certification		UL1449 ed.5

Part number

480571