



DACF25S-20-275



- ✦ Type 2 AC surge protector
- ✦ In: 15 kA
- ✦ I_{max}: 25 kA
- ✦ Interne Disconnection device
- ✦ Pluggable module for each phase
- ✦ Remote signaling
- ✦ EN 61643-11, IEC 61643-11 certified
- ✦ UL1449 ed.5 compliance



Electrical Characteristics		
SPD type	IEC	2
Network		230 V single-phase
AC system		TN
Max. AC operating voltage	U _c	275 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection
Residual Current Leakage current to Ground	I _{pe}	< 1 mA
Follow current	I _f	None
Nominal discharge current 15 x 8/20 µs impulses	I _n	15 kA
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	25 kA
Total Maximum discharge current max. total withstand @ 8/20 µs	I _{max} Total	50 kA
Connection mode(s)		L/PE and N/PE
Protection level N/PE @ I _n (8/20µs)	Up N/PE	1.25 kV
Protection level L/PE @ I _n (8/20µs)	Up L/PE	1.25 kV
Protection level N/PE at 5 kA @ 5 kA (8/20µs)	Up-5kA	1 kV
Residual voltage L/PE at 5 kA @ 5 kA (8/20µs)	Up-5kA	1 kV
Admissible short-circuit current	I _{sc}	100 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole - Red/Green
Spare module(s)		MDACF25-275
Remote signaling of disconnection		Output on changeover contact
Wiring for remote signaling		1.5 mm ² max.
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions		See diagram - 2TE (EN43880)
Weight		0.208 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		internal (equivalent AC rating : 40 A, gG Type)
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		KEMA
Part number		
821410222		