





CITEL



Type 2 AC Surge Protector for PCB mounting

PAC25S-10-420

- Type 2 AC surge protector
- PCB mounting
- I_{max}: 25 kA
- Remote signaling
- EN 50539-11 and IEC 61643-31 compliance*



Electrical Characteristics

SPD type	IEC	2
Max. AC operating voltage	Uc	420 Vac
Nominal discharge current <i>15 x 8/20 μs impulses</i>	In	10 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	25 kA
Protection level <i>@ In (8/20 μs)</i>	Up	1.8 kV
Admissible short-circuit current	I _{sc}	25 000 A

Mechanical Characteristics

Connection to Network	Through soldering pins
Mounting	On Printed Circuit Board
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Disconnection indicator	1 mechanical indicator
Remote signaling of disconnection	Output on changeover contact
Dimensions	9.6 mm
Weight	0.020 kg
Weight	0.034 kg

Disconnectors

Thermal disconnector	Internal
----------------------	----------

Standards

Standards compliance	EN 61643-11 / IEC 61643-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.
----------------------	---

Part number

8711201

