





CITEL

1-pair DIN rail plug-in Data surge protector

DLA-06D2/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode

Electrical Characteristics

Network		RS422, RS485
Nominal line voltage	Un	6 V
Max. DC operating voltage	Uc	8 Vdc
Cut-off frequency -3dB, 100 ohm system	f max.	> 75 MHz
Cut-off frequency -1dB, 100 ohm system	f max.	> 30 MHz
Max. load current @25°C	IL	600 mA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA
Nominal discharge current C2 Category	In	10 kA
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-Y (Line/Line)	Up	30 V
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-C (Line/Earth)	Up	650 V
Max. capacitance	C	< 50 pF
Impulse current D1 (10/350µs), 2 applications, X-C (Line/Earth)	Iimp	5 kA
Line resistance (± 10%)		2 Ohm

Mechanical Characteristics

Technology	GDT+TVS diode
SPD configuration	1-pair+shielded
Connection to Network	Spring terminal: cross section 0.5-2.5mm²
Format	Din Rail Base-Plug-in Module
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating and storage temperature	-40/+85°C
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Spare module(s)	DLAM-06D2
Dimensions	See diagram

Standards

Standards compliance	IEC 61643-21 / EN 61643-21
----------------------	----------------------------

Part number

6401612

