





- ✦ Din rail plug-in surge protector
- ✦ 2-pair
- ✦ Un: 48 V
- ✦ Shield wire protection
- ✦ Without line cut-off
- ✦ IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode

Electrical Characteristics

Network		Fipway, WorldFIP, FieldBus-h2
Nominal line voltage	Un	48 V
Max. DC operating voltage	Uc	53 Vdc
Max. frequency	f max.	20 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	300 mA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	75 V
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	75 V
Max. capacitance	C	< 50 pF
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA
Nominal discharge current C2 Category	In	5 kA
Line resistance (± 10%)		4.7 Ohm

Mechanical Characteristics

Technology	GDT+TVS diode
SPD configuration	2-pairs+shielded
Connection to Network	By screw terminal: cross section 0.5-2.5mm²
Format	Plug-in DIN box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating and storage temperature	-40/+85°C
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Spare module(s)	DLA2M-48dBC
Dimensions	See diagram
Weight	0.089 kg

Standards

Standards compliance	IEC 61643-21 / EN 61643-21
----------------------	----------------------------

Part number

640314